



Notes:

- 1) Dimmers live upstage right
- 2) 400amp 3Phase power is located downstage left
- 3) Down stage truss shown on House Points
- 4) Upstage truss = (60) 1k Narrow Par 64s
- 5) Downstage truss = (60) 1k Medium Par 64s
 - (6) ETC Source 4 750w 26deg Lekos
 - (2) TMB 8 lite mole fays

Venue: The Tower Theater

Lighting Co: Pin Point Lighting

Lighting Designer:

Email:

Drawn By: Jason "Toecutter" Olson

Phone: (610)357-3081

Email: toecutter@pinpointlighting.com

Crew Chief: Lighting L2:

THIS DRAWING REPRESENTS
VISUAL CONCEPTS AND
CONSTRUCTION SUGGESTIONS
ONLY. THE DESIGNER IS NOT
QUALIFIED TO DETERMINE THE
STRUCTURAL

APPROPRIATENESS OF THIS
DESIGN AND WILL NOT ASSUME
RESPONSIBILITY FOR IMPROPER
ENGINEERING, CONSTRUCTION,
OR HANDLING. ALL MATERIALS,
FINISHES, AND CONSTRUCTION
MUST COMPLY WITH THE MOST
STRINGENT FIRE AND SAFETY
CODES AS APPLICABLE.





